


## NOTES:

- 1. THIS DRAWING IS A GUIDELINE BASED ON SSF MUNI CODE 20.300.017.A. CASES NOT ADDRESSED BY THIS SHEET OR THE MUNI CODE SHALL REQUIRE CITY ENGINEER APPROVAL.
- 2. TRAFFIC SIGHT TRIANGLE SHALL BE MEASURED 35' FROM THE INTERSECTION POINT OF THE PROPERTY LINES.
- VEGETATION, FENCES, OR OTHER STRUCTURES SHALL BE NO TALLER THAN 30" ABOVE THE CURB WITHIN TRAFFIC SIGHT TRIANGLE.
- TREES SHALL BE TRIMMED BACK TO THE TRUNK AT LEAST 8' ABOVE THE CURB.
- THE FOLLOWING ARE EXEMPT FROM THESE RESTRICTIONS:
  a. PERMANENT BUILDINGS
  - b. UTILITY POLES
  - c. CITY SIGNAGE OR SIGNALS
  - d. PLANTS IN OPEN GROWTH HABITATS THAT DO NOT FORM A HEDGE AND TRIMMED TO LEAVE UNOBSTRUCTED CROSS VISIBILITY.
  - e. WHERE THE GROUND CONTOUR PHYSICALLY CONSTRICTS CROSS VISIBILITY.



SOUTH SAN FRANCISCO PUBLIC WORKS ENGINEERING

SIGHT TRIANGLE CORNER VISIBILITY

**DEC 2020** 

**A-6A**